

3.7 OIL FIELD SERIES

Oil Field Series Overview

60FG / 65FG

The Oil Field Series trailers from Talbert Manufacturing are built to meet the rugged demands of hauling equipment to and from oil field sites. Built from high-strength 100,000 P.S.I. minimum yield steel, the Oil Field Series trailers can handle the harsh conditions of drill site loading and unloading.



60FG



65FG

3.7 OIL FIELD SERIES

Specification Chart

MODELS	Drop Deck Oil Field	60FG Oil Field	65FG Oil Field
CAPACITY	110,000 lbs. Distributed 70,000 lbs. in 10 ft.	120,000 lbs. Distributed 110,000 lbs. in 16 ft.	130,000 lbs. Distributed 120,000 lbs. in 16 ft.
ESTIMATED WEIGHT	Starting at 17,150 lbs.	Starting at 27,160 lbs.	Starting at 31,100 lbs.
UNIQUE FEATURE	Load Bearing Rolling Tail Board at Rear Full Width with Spherical Bearings, Two Sets Overload Bearings Below, and Pin Pockets in Outside Flange at 45 Degree Angle		
CONSTRUCTION	T1 & 80K Beams	T1 Beams	
SWING CLEARANCE	11 ft. 0 in. Upper 30-in. Kingpin Setting	108-in. Swing Radius with Alternate Setting at 96-in.	120-in. Swing Radius with Alternate Settings at 108-in., 96-in.
DIMENSIONS	48 & 53 ft. OAL 8 ft. 6 in. Wide	Starting at 53 ft. OAL (not including tail roller) 8 ft. 6 in. Wide	Starting at 59 ft. OAL (not including tail roller) 8 ft. 6 in. Wide
LOADED DECK HEIGHT	35-42 in.		
TIRES	Low Profile 17.5 Tires / Low Profile 22.5 Tires		
SUSPENSION	Ridewell Air Ride Suspension		
FLOORING	1-1/8 in. Shiplap Apitong Flooring	2 in. Apitong Flooring	
LIGHTS	DOT Rubber Mount with Modular Harness		
ADDITIONAL SPECIFICATIONS	<ul style="list-style-type: none"> Winch Cable Pipe on Rear of Gooseneck One Pipe Pocket Each End of Rear Gooseneck Pipe Four Pin Pockets Each Side of Lower Deck - Inside Rub Rails 	<ul style="list-style-type: none"> Fixed Gooseneck Narrow Type with High Arch Profile Cable Roller with Spherical Bearings Between Gooseneck Mainbeams at Rear, Pin Pockets in Front of Roller Cable Pick-Up Eye with Winch Lug for Connection Point Removable Plate Between Gooseneck Mainbeams to Walk on Two Pair Air Pop-Up Rollers Each Side Air Lift Axle(S) (60FG Axle 4 / 65FG Axle 1 & 5) Lash Rings Ten Each Side of Deck Key Hole Slots in Outer Flange on 48 in. Centers Six Pin Pockets on Outside Flange (Including Tail Roller) Two Pair of Pipe Pockets Inside Side Beam Flange Axle Stops on Last Axle to Prevent Crushing when Loading Lightening Holes in Deck Side Beams 	